



DriveDOCK Extreme

EXTRMDD



Handsfree



Bluetooth



SOS



Track



Voice




Data



USB



Charging



BEAM

DriveDOCK Extreme

EXTRMDD

- ▶ **Handsfree**
- ▶ **Bluetooth**
- ▶ **SOS Support**
- ▶ **Extreme Tracking**
- ▶ **Support Ext GPS Antenna**



BEAM's **DriveDOCK Extreme** hands-free docking solution provides a high quality transport installation for the Iridium Extreme handset. The docking station has in-built echo cancelling and full duplex technologies to provide superior voice quality and professional hands-free or privacy calls for any vehicle, boat or aircraft*.

The Iridium Extreme handset fits securely in the dock, which features USB data connectivity, phone charging and integrated antenna, data and power connection making it possible to keep all antenna cables and power permanently connected to the **DriveDOCK** ready for use.

The Iridium Extreme handset fits securely in the docking station with an easy click to lock mechanism that can be inserted and removed with a press of a button. It is purposely built to allow you to utilize the SOS emergency button whilst docked.

DriveDOCK Extreme also supports the use of an optional Intelligent Privacy Handset, that replicates the full functionality of the Extreme handset in another location.

* Independent Aeronautical certification MUST be gained prior to installation.




Trucks



**Motor Homes
/ Recreational
Vehicles**



**Position
Reporting**



**Emergency
Services**

KEY FEATURES

▶ DriveDOCK Extreme CRADLE

- Securely holds Extreme handset
- Robust design and construction
- Charges Extreme handset ready for use
- Integrated antenna connection, Iridium and GPS
- Integrated USB connectivity

▶ HANDSFREE MODE

- In-built echo cancelling
- Full duplex technology
- Superior voice quality

▶ TRACKING

- Triggering of Quick GPS
- Interfaces to BEAM's MyBuddy Extreme Portal

▶ PANIC/ALERTS

- Option of additional wired SOS alert buttons
- Interfaces to BEAM's MyBuddy Extreme
- Supports Iridium Extreme SOS

▶ INTEGRATED BLUETOOTH®

- Bluetooth® in-built to cradle
- Supports Bluetooth® voice connectivity

▶ IN-BUILT RINGER

- In-built ringer for enhanced ring indication
- Loud ring indication via external speaker

▶ VOICE, DATA, SMS, SBD

- Supports all Iridium voice, data, SMS & SBD services

▶ PRIVACY HANDSET (Optional) RST755

- Supports optional Beam privacy handset
- Auto sensing answer intelligence
- Switches between handset and handsfree modes

▶ INTELLIGENT HANDSET (Optional) RST970

- Supports optional Intelligent handset

▶ INSTALLATION

- Supports 9 - 32V DC power input
- Installation via universal mount, also suitable for wall mounting
- Antenna, microphone and speaker installed in a convenient location

▶ QUALITY

- 2 year replacement guarantee for peace of mind
- 100% factory tested
- Fully certified, Iridium, RoHS, CE, AS/EN60950

MyBuddy WEB APPLICATION

MyBuddyExtreme.com is a web based tracking application that can be accessed from any computer via the internet. It features alert, tracking/monitoring and fleet management providing global access to monitor personnel anywhere in the world via the Iridium Extreme handheld phone. MyBuddy's secure web portal, allows access to view high quality global street level maps and satellite imagery to easily pin-point asset locations and areas of incidence.

MyBuddy supports advanced features such as alert reporting, SMS & Email alerts, track/trace capabilities, automatic asset clustering & automatic map sizing.

Visit: www.mybuddyextreme.com



TECHNICAL SPECIFICATIONS

POWER SPECIFICATIONS		ENVIRONMENTAL	
Rated Input	9-32V DC, 2A max	Operate Temp. Range*	DriveDOCK Extreme -30°C to +70°C
Average Power Consumption	Current @ 12VDC, Watts	Charging Temp. Range#	0°C to 45°C
Standby	70mA 0.84W	Operating Humidity Range	< 85% RH non-condensing
Transmit + Charging	0.7A 8.4W	Storage Temperature	-30°C to +85°C
Sleep Mode	5mA 60mW	Weight	Cradle 0.48kg (1.1 lbs)
INTERFACES		EMC Compliance	EN301489-1/-20
External Speaker and Microphone	One horizontal 2-pin Microfit connector on the cable loom for speaker and one vertical 2-pin Microfit connector for microphone.	RoHS	Full compliant RoHS Directive EU 2002/95/EC (All 6 substances)
Privacy Handset (Line In/Out)	4-pole 3.5mm audio jack at the bottom of the DriveDOCK cradle.	WEEE	For EU countries, this product must be collected separately from household waste, as defined in each region. This product must not be discarded together with household waste.
Data Port (USB)	USB Mini-B 5-pin female (USB Slave). USB 2.0 compliant, CDC Serial profile.	Flame Retardant	UL94.0
Alarm (Alert) Loop 1 input, 1 output	Alarm Mode: "Normally-Closed" Loop IN to OUT Up to 50m cable run/multiple buttons in series. Brown wire is Input, Green wire is Output.	Safety - SELV	AS/NZ 60950-1
Power Cable	4-way Microfit socket. +Vin (Red wire), 0V (GND, Black wire), and ACC (On/Off Sense, Yellow wire). 9-32VDC tolerant. ACC sense: High(1) > +7Vdc Low (0) 0V < +5Vdc	* When 9575 Battery is fully charged # Derived from the charging temperature range of the Iridium 9575 handset battery.	
Horn Output / Audio System Mute	Blue wire on the cable loom. Open collector output can be interfaced to 12V or 24V DC with up to 120mA current sink capability.	BLUETOOTH® MODULE (INTERNAL)	
KIT CONTENTS		System	Bluetooth® 2.0v+EDR (Enhanced Data Rates), 802.11 coexistence.
DriveDOCK Extreme Cradle		Profiles	HFP - Hands-Free Profile v.1.5 HFP-AG - Hands-Free Audio Gateway Profile v.1.5 & SPP - Serial Port Profile
Universal Mounting Bracket (RAM)		Power	Default = Class 2 (< 10 metres). 2.4GHz - 2.4835GHz Unlicensed ISM Band
DC Power Cable / Fuse Kit		Antenna	Integrated chip antenna
Speaker		Regulatory	Bluetooth® identifier: B03005. CE 89/336/EEC - #EC/2006/20013C. FCC part 15 class B: DriveDOCK contains Transmitter Module FCC ID: GQGWT11. Canada: Cert# 5123A-BGTWT11E Japan: 07215089/AA/00
Microphone		Legal	The Bluetooth® word, mark and logos are owned by the Bluetooth® SIG, Inc. and any use of such marks by BEAM Communications is under license. Other trademarks and trade names are those of their respective owners.
Quick Start Guide			
User Manual			

ACCESSORIES

RST710	Iridium Mast Mount Antenna
RST714	Iridium Whip Antenna
RST715	Iridium Magnetic Mount
RST720	Iridium Bolt Mount Antenna
RST702	Dual Mode Iridium/GPS Mast Antenna
RST705	Dual Mode Iridium/GPS Magnetic Antenna
RST706	Dual Mode Iridium/GPS Whip Antenna

RST755	Beam Privacy Handset Kit
RST970	Intelligent Handset
RST932	Antenna Cable 6m / 18f
RST933	Antenna Cable 12m/36f
RST410	Emergency push button / cable
RST055A	UPS Battery Pack MyBuddy Extreme

APPROVED BEAM RESELLER

www.beamcommunications.com

EXTRMDD_REV01_11/11

AFRICA

ASIA

AUSTRALIA

EUROPE

MIDDLE EAST

NORTH AMERICA

SOUTH AMERICA