

iridium PotsDOCK 9555

9555PD





PotsDOCK 9555 is an intelligent compact docking station specifically designed for the Iridium 9555 satellite handset. PotsDOCK allows the 9555 handset to be used in a wide variety of applications using an intelligent RJ11/POTS connectivity that supports standard corded, cordless or DECT handsets, or alternatively interfaced with a PBX system.

PotsDOCK also has an in-built Bluetooth® module for voice connectivity along with an intelligent tracking and alert reporting system that can be easily configured to support periodic polling or emergency alert reporting.

The cleverly designed PotsDOCK cradle simply and securely docks the Iridium 9555 handset into place ready for use and fully integrates antenna, power and data connectivity into a single streamline unit.

The 9555 handset is easily inserted and removed by the press of a button on the top of the dock, making it very easy for use out of the dock at anytime.

PotsDOCK also supports the use of an optional compact Beam Privacy Handset that can be located next to the PotsDOCK for added convenience if required.







Motor Homes / Recreational Vehicles



Cruise Ship / Large Vessels



Position Reporting



Emergency Services

KEY FEATURES

POTSDOCK 9555 CRADLE

- Securely holds 9555 handset
- Robust design and construction
- Charges 9555 handset ready for use
- Integrated antenna connection
- Integrated USB connectivity

POTS/RJ11

- Supports standard cordless & corded telephones (5 REN)
- RJ11 can be run 600m (2000 ft) from unit
- · Corded, cordless or DECT handsets
- Easily integrated to PBX system
- Ring, busy & dial tones
- Superior voice quality

TRACKING/GPS

- Tracking & alert monitoring capable
- · Periodic position reports or remotely polled
- Triggered position status message
- In-built GPS engine
- Also compatible with other tracking applications

PANIC/ALERTS

- · Panic alert button in-built to cradle
- Option of additional wired alert buttons

INTEGRATED BLUETOOTH®

- Bluetooth® in-built in cradle
- Supports Bluetooth® voice accessories

IN-BUILT RINGER

• In-built ringer for enhanced ring indication

VOICE, DATA, SMS, SBD

- Supports all Iridium voice, data, SMS & SBD
- Access to prepaid, post paid & crew calling

PRIVACY HANDSET

- Supports optional Beam privacy handset
- Auto sensing answer/hang-up intelligence

INSTALLATION

- Supports 9 32V DC power input
- Flexible installation via universal mount, also suitable for wall mounting
- Supplied with 110 240V AC Plug pack
- Handset always charged ready for use

QUALITY

- Professional industrial design
- 2 year peace of mind with a replacement guarantee
- 100% factory tested
- Full certified, Iridium, RoHS, CE, IEC60945

TRACKING / ALERT MONITORING

PotsDOCK has an in-built GPS module that can provide simple tracking, monitoring and alert management in various applications within various types of vehicles, vessels or fixed site locations.

The GPS provides pinpoint accuracy and enables tracking worldwide. Tracking and alert messages can be sent via SMS or Short Burst Data, if provisioned on the handset.

PotsDOCK's tracking and alert messages can be simply sent via SMS or email address as required.

Tracking messages can be sent from the PotsDOCK via the following means;

- 1. Periodic position reporting, preset during configuration of the terminal
- 2. Upon an alert being activated via the Alert button on the cradle or connected alert button
- 3. A current location position can be sent at any time by pressing the Track button on the front of the PotsDOCK

Alert/Alarm messages can be activated on the PotsDOCK using the two button press on the front of the cradle or alternatively an additional alert button or other trigger can be connected to the unit.

Once configured the alert system is always on and will generate an alert message to the preset destination once triggered. Alerts can be triggered to continually send until the alert is cleared either remotely or locally on the PotsDOCK unit.

EQUIPMENT OVERVIEW





TECHNICAL SPECIFICATIONS

IRIDIUM NETWORK		
9555 Handset	1616 - 1625 MHz	
Compressed Data	10 - 12 kbps	
Voice/Data Modulation	2.4 kbps	
POWER SPECIFICATIONS		
Power input voltage	9 - 32 V DC, 2A max	
Power Consumption at 12V DC		
Stand-by (when battery charged) - incl handset & RJ11	1.1W (90mA @ 12Vin)	
Transmit - incl handset & RJ11	6W (0,5A @ 12Vin)	
GPS MODULE		
Channels	14 tracking, 51 Channel Acquiring	
Update Rate	1Hz	
Accuracy	Position 2.5mCEP, Velocity 0.1m/s, Timing 300ns	
Acquisition TTFF	Cold 29sec, Hot 1sec	
Sensitivity	–161 dBm	
Operational Limits	Altitude 18000m , Velocity 515m/s	
Dynamics		4G
PHYSICAL SPECIFICATIONS	UNIT ONLY	PACKED
Dimensions - mm	200 x 75 x 65	325 x 140 x 88
Dimensions - inches	7.9 x 3.0 x 2.6	12.8 x 5.5 x 3.5
Weight - kg	0.32	1.3
Weight - lbs	0.7	2.86
ENVIRONMENT SPECIFICATIONS		
Operating Temperature	-30 to +70 °C	-22 to +158 °F
Storage Temperature	-40 to +85 °C	-40 to 185 °F
Humidity	93% non condensing	
I/O ALARM / ALERT		
Alert Button	In-built on PotsDOCK - 2 Key Press	
1 x Alarm Loop	Bare Wire - "Normally Closed" Loop IN to OUT	
	Up to 500m cable run/multi buttons	
Track	Inbuilt - single key press	

CONNECTORS/INTERFACES		
POTS/RJ11	RJ11/2-wire, complex or 600 Ω , 5REN	
	600m adjustable dial/busy tones/frequency, adaptive Z	
Iridium - Antenna	Fixed Cable to TNC-Female	
GPS-Antenna	Fixed Cable to SMA-Female	
9-32 V DC	4-way microFit (AC/DC adator, or DC lead)	
Privacy Handset Port	4 pole 3.5mm jack	
Data Port	USB Mini Base of Dock	
Bluetooth® Voice only	Inbuilt module/antenna, class 1 (up to 300m) Bluetooth® system 2.0v+EDR, CE and FCC	
BUTTONS/LEDs		
Bluetooth®	Blue/Orange	
Alert	Red/Orange	
Mute/Ringer	Red	
Backlight	White LED	
Handset Release	Top of Cradle, No LED	
CERTIFICATIONS		
Iridium Approved		
Electrical Safety		
EMC Compliance		
CE Compliance		
RoHS		
C Tick		
Independant Aeronautical ce	rtification MUST be gained prior installation	
KIT CONTENTS		
Beam PotsDOCK Cradle		
Universal Mounting Brack	ket (RAM)	
110 - 240V AC Plug Pack	(
9 - 32V DC Power Cable		
Quick Start Guide		
User Manual		

ACCESSORIES

RST702 Dual I RST705 Dual I RST710 Iridiur RST715 Iridiur

RST725

Γ

Dual Mode Iridium/GPS Mast Mount Antenna
Dual Mode Iridium/GPS Magnetic Mount with 6m of cable
Iridium Mast Mount Antenna
Iridium Magnetic Mount incl 5m of cable
Bluetooth® Headset incl car charger

RST755 RST932 RST933

RST942

RST923

Beam Privacy Handset 6m/18ft Iridium Cable Kit 12m/36ft Iridium Cable Kit 6m/18ft GPS Cable 12m/36ft GPS Cable

APPROVED BEAM RESELLER

www.beamcommunications.com

+61 3 8588 4500



+61 3 9560 9055



info@beamcommunications.com

9555PD_REV02_04/13

AFRICA ASIA AUSTRALIA EUROPE MIDDLE EAST NORTH AMERICA SOUTH AMERICA