# iridium ···· iridium Iridium : iridium LARC 300 6 440 9 11117

### **DriveDOCK Extreme**

EXTRMDD



DriveDO



## DriveDOCK Extreme



BEAM's **DriveDOCK Extreme** hands-free docking solution provides a high quality transport installation for the Iridium Extreme handset. The docking station has in-built echo cancelling and full duplex technologies to provide superior voice quality and professional hands-free or privacy calls for any vehicle, boat or aircraft\*.

The Iridium Extreme handset fits securely in the dock, which features USB data connectivity, phone charging and integrated antenna, data and power connection making it possible to keep all antenna cables and power permanently connected to the **DriveDOCK** ready for use.

The Iridium Extreme handset fits securely in the docking station with an easy click to lock mechanism that can be inserted and removed with a press of a button. It is purposely built to allow you to utilize the SOS emergency button whilst docked.

**DriveDOCK** Extreme also supports the use of an optional Intelligent Privacy Handset, that replicates the full functionality of the Extreme handset in another location.

\* Independent Aeronautical certification MUST be gained prior to installation.





Motor Homes / Recreational Vehicles



Position Reporting



Emergency Services



#### **KEY FEATURES**

#### DriveDOCK Extreme CRADLE

- Securely holds Extreme handset
- Robust design and construction
- Charges Extreme handset ready for use
- Integrated antenna connection, Iridium and GPS
- Integrated USB connectivity

#### HANDSFREE MODE

- In-built echo cancelling
- Full duplex technology
- Superior voice quality

#### **TRACKING**

- Triggering of Quick GPS
- Interfaces to BEAM's MyBuddy Extreme Portal

#### **PANIC/ALERTS**

- Option of additional wired SOS alert buttons
- Interfaces to BEAM's MyBuddy Extreme
- Supports Iridium Extreme SOS

#### INTEGRATED BLUETOOTH®

- Bluetooth® in-built to cradle
- Supports Bluetooth® voice connectivity

#### IN-BUILT RINGER

- In-built ringer for enhanced ring indication
- Loud ring indication via external speaker

#### VOICE, DATA, SMS, SBD

 Supports all Iridium voice, data, SMS & SBD services

#### PRIVACY HANDSET (Optional) RST755

- Supports optional Beam privacy handset
- Auto sensing answer intelligence
- Switches between handset and handsfree modes

#### INTELLIGENT HANDSET (Optional) RST970

• Supports optional Intelligent handset

#### **INSTALLATION**

- Supports 9 32V DC power input
- Installation via universal mount, also suitable for wall mounting
- Antenna, microphone and speaker installed in a convenient location

#### QUALITY

- 2 year replacement guarantee for peace of mind
- 100% factory tested
- Fully certified, Iridium, RoHS, CE, AS/EN60950

#### MyBuddy WEB APPLICATION

MyBuddyExtreme.com is a web based tracking application that can be accessed from any computer via the internet. It features alert, tracking/ monitoring and fleet management providing global access to monitor personnel anywhere in the world via the Iridium Extreme handheld phone. MyBuddy's secure web portal, allows access to view high quality global street level maps and satellite imagery to easily pin-point asset locations and areas of incidence.

MyBuddy supports advanced features such as alert reporting, SMS & Email alerts, track/trace capabilities, automatic asset clustering & automatic map sizing.

Visit: www.mybuddyextreme.com



### TECHNICAL SPECIFICATIONS

POWER SPECIFICATIONS			
Rated Input	9-32V DC, 2A max		
Average Power Consumption	Current @ 12VDC, Watts		
Standby	70mA 0.84W		
Transmit + Charging	0.7A 8.4W		
Sleep Mode	5mA 60mW		
INTERFACES			
External Speaker and Microphone	One horizontal 2-pin Microfit connector on the cable loom for speaker and one vertical 2-pin Microfit connector for microphone.		
Privacy Handset (Line In/Out)	4-pole 3.5mm audio jack at the bottom of the DriveDOCK cradle.		
Data Port (USB)	USB Mini-B 5-pin female (USB Slave). USB 2.0 compliant, CDC Serial profile.		
Alarm (Alert) Loop 1 input, 1 output	Alarm Mode: "Normally-Closed" Loo IN to OUT Up to 50m cable run, multiple buttons in serie: Brown wire is Inpu Green wire is Outpu		
Power Cable	4-way Microfit socket. +Vin (Red wire), OV (GND, Black wire), and ACC (On/ Off Sense, Yellow wire). 9-32VDC tolerant. ACC sense: High(1) > +7Vdc Low (0) OV < +5Vdc		
Horn Output / Audio System Mute	Blue wire on the cable loor Open collector output can b interfaced 12V or 24V DC with up to 120m current sink capabilit		
KIT CONTENTS			
DriveDOCK Extreme Cradle			
Universal Mounting Bracket (RAM)			
DC Power Cable / Fuse Kit			
Speaker			
Microphone			
Quick Start Guide			
User Manual			

Operate Temp. Range*	DriveDOCK Extreme -30°C to +70°
Charging Temp. Range#	0°C to 45°
Operating Humidity Range	< 85% RH non-condensin
Storage Temperature	-30°C to +85°
Weight	Cradle 0.48kg (1.1 lbs
EMC Compliance	EN301489-1/-2
RoHS	Full compliant RoHS Directive EU 2002/95, EC (All 6 substances
WEEE	For EU countries, this product must b collected separately from household waste, a defined in each region. This product must no be discarded together with household wast
Flame Retardant	UL94.
Safety - SELV	AS/NZ 60950-
	,
* When 9575 Battery is fully	/
* When 9575 Battery is full # Derived from the charging battery.	/ charged temperature range of the Iridium 9575 handset
* When 9575 Battery is fully # Derived from the charging battery. BLUETOOTH® MODULE	y charged temperature range of the Iridium 9575 handset (INTERNAL) Bluetooth® 2.0v+EDR (Enhanced Data Rates 802.11 coexistenc: HFP - Hands-Free Profile v.1. HFP-AG - Hands-Free Audio Gateway Profil
* When 9575 Battery is full # Derived from the charging battery. BLUETOOTH® MODULE System	y charged temperature range of the Iridium 9575 handset (INTERNAL) Bluetooth® 2.0v+EDR (Enhanced Data Rates
* When 9575 Battery is fully # Derived from the charging battery. BLUETOOTH® MODULE System Profiles	k charged temperature range of the Iridium 9575 handset (INTERNAL) Bluetooth® 2.0v+EDR (Enhanced Data Rates 802.11 coexistenci HFP - Hands-Free Profile v.1. HFP-AG - Hands-Free Audio Gateway Profil v.1.5 & SPP - Serial Port Profil Default = Class 2 (< 10 metres
* When 9575 Battery is fully # Derived from the charging battery. BLUETOOTH® MODULE System Profiles Power	(INTERNAL) Bluetooth® 2.0v+EDR (Enhanced Data Rates 802.11 coexistence HFP - Hands-Free Profile v.1. HFP-AG - Hands-Free Audio Gateway Profi v.1.5 & SPP - Serial Port Profil Default = Class 2 (< 10 metres 2.4GHz - 2.4835GHz Unlicensed ISM Ban

AC	CESSORIES		
RST710	Iridium Mast Mount Antenna	RST755	Beam Privacy Handset Kit
RST714	Iridium Whip Antenna	RST970	Intelligent Handset
RST715	Iridium Magnetic Mount	RST932	Antenna Cable 6m / 18f
RST720	Iridium Bolt Mount Antenna	RST933	Antenna Cable 12m/36f
RST702	Dual Mode Iridium/GPS Mast Antenna	RST410	Emergency push button / cable
RST705	Dual Mode Iridium/GPS Magnetic Antenna	RST055A	UPS Battery Pack
RST706	Dual Mode Iridium/GPS Whip Antenna		MyBuddy Extreme

Ē

APPROVED BEAM RESELLERI

L

#### www.beamcommunications.com

EXTRMDD\_REV01\_11/11

ASIA

AFRICA

AUSTRALIA

EUROPE

MIDDLE EAST

NORTH AMERICA

SOUTH AMERICA

7

4